

novaflo™

**HDPE, SINGLE WALL LAND DRAINAGE PIPE,
CORRUGATED BORE, SLOTTED,**

Code Explanation	
Product Code	Coil length (metres)
400-110-100	
	OD (mm)



Novaflo, slotted, coloured black

novacoil™

**HDPE SINGLE WALL DUCT PIPE,
CORRUGATED BORE, UNSLOTTED**

Code Explanation	
Product Code	Coil length (metres)
500.110.100	
	OD (mm)



Novacoil, unslotted, coloured black with White Stripe

NOVAFLO™ is a single wall corrugated high density polyethylene land drainage pipe. NOVAFLO™ has been a leading brand name in the rural New Zealand land drainage market for over twenty years. During this time farmers have learned to rely on this quality product for delivering excellent drainage results. Such benefits as improved soil structure, larger root systems, better fertiliser uptake and reduction in surface pugging has made the use of NOVAFLO™ an integral part of the New Zealand farmer's search for greater productivity. Novacoil is the unslotted version of NOVAFLO™.

Features and Benefits of Novaflo and Novacoil

- | | |
|------------------------|---|
| <i>Coupling</i> | • All sizes are provided with a factory fitted, end load resistant coupler on each coil |
| <i>Corrugated wall</i> | • Corrugated pipe wall, gives buried structural performance |
| <i>Flexible</i> | • Pipe flexibility assists with pipe handling and location during installation |
| <i>Fittings</i> | • Compatible with commercially available injection moulded, fabricated PVC fittings to assist with greater flexibility of use. |
| <i>Choice</i> | • Available in three diameters allowing a degree of choice to match the performance requirement. |
| <i>Durable</i> | • Manufactured from high density polyethylene, a plastic material which is impact resistant, rust proof, abrasion resistant, and durable for in-ground service. |
| <i>Quality</i> | • Manufactured in New Zealand by Iplex Pipelines using a Quality Management System accredited to AS/NZS ISO 9001:2008. |
| <i>Visible</i> | • NEXUSCOIL is colour coded with a white stripe to visually distinguish it as being unslotted and aid identification |
| <i>Recycled HDPE</i> | • Pipe contains significant proportions of Post Consumer Recycled HDPE material, derived from sources within New Zealand |



Trenched Installation of 110mm Iplex NOVAFLO subsoil drainage pipe, in 450m rolls, using laser-guided gradient control

Product Range

Product	Product Code	Nominal OD (mm)	Length or Coil Size (m)	Colour
NOVAFLO™ (Punched) * sold only in bundles of 4 coils	400.065.15	65	15	● Black
	400.065.30	65	30	● Black
	400.065.150	65	150	● Black
	400.110.15	110	15	● Black
	400.110.30	110	30	● Black
	400.110.50	110	50	● Black
	400.110.100	110	100	● Black
	400.110.450	110	450	● Black
	400.160.15	160	15	● Black
	400.160.45	160	45	● Black
	400.160.185	160	185	● Black
NOVACOIL™ (Unpunched)	500.065.15	65	15	● Black w/ White Stripe
	500.065.30	65	30	● Black w/ White Stripe
	500.065.150	65	150	● Black w/ White Stripe
	500.110.15	110	15	● Black w/ White Stripe
	500.110.30	110	30	● Black w/ White Stripe
	500.110.100	110	100	● Black w/ White Stripe
	500.160.15	160	15	● Black w/ White Stripe
	500.160.45	160	45	● Black w/ White Stripe

NOVAFLO™ Fittings

Compatible range of PVC and PE fittings for use with the NEXUS™ and NOVAFLO™ range of pipes.

45° Reducing Junction F&F		45° Plain Junction F&F		Level Invert F&F	
					
Size (mm)	Product Code	Size (mm)	Product Code	Size (mm)	Product Code
110 x 45	104.100.45	65 x 45	104.65.45	160 x 110	123.160.110S
160 x 45	04.160.45			Soc eted both ends	
160 x 110 x 45	04.160.110.45				

Coupler F&F		Coupler F&F		End Plug	
					
Size (mm)	Product Code	Size (mm)	Product Code	Size (mm)	Product Code
65	410.065	110	420.110	110	430.110
		160	420.160	160	430.160
		200	420.200		